

94	Manufacturer	Design	Frame	Rated-power kW	RPM_FL min <sup>-1</sup>		Voltage V	connection	Frequency Hz	Enclosure	temp rise K	Insulation_Class	Eff_FL %	Eff_75 %	Eff_50 %	Eff_25 %	Efficiency_class	PF_FL	PF_75	PF_50	PF_25	Torque_FL Nm	DOL_Starting_vs FL_Torque (%)	Star_Delta_Starting vs_FL_Torque (%)	DOL_Pull_up_vs FL_Torque (%)	Star_Delta_Pull_up vs_FL_Torque (%)	DOL_Pull_out_vs FL_Torque (%)	Star_Delta_Pull_out vs_FL_Torque (%)		
94	Dutchi Motors B.V.	DM1-	132 MX4	9	1435	400	/	690	Δ	Y	50	IP 55	78,7	F (temp. rise B (80 K))	86,84694	87,47803	86,31822	79,82379	N/A	0,83696	0,78847	0,67556	0,44953	59,89547	2,555439209	0,798574753	1,832518906	0,572662158	3,429668412	1,071771379
5,56	Dutchi Motors B.V.	DM1-	132 MX6	5,5	975	400	/	690	Δ	Y	50	IP 55	69,2	F (temp. rise B (80 K))	85,6	85,2	85,0	74,0	N/A	0,77	0,69	0,64	0,35	54	2,1	0,64	1,70	0,53	4,0	1,26
7,54	Dutchi Motors B.V.	DM1-	132 M4	7,5	1452	400	/	690	Δ	Y	50	IP 55	73,0	F (temp. rise B (80 K))	87,0	88,1	87,5	82,3	EFF 2	0,86	0,82	0,72	0,51	49	2,4	0,76	1,74	0,54	3,2	1,01
38	Dutchi Motors B.V.	DM1-	132 M8	3	710	400	/	690	Δ	Y	50	IP 55	59,6	F (temp. rise B (80 K))	80,7	81,2	78,6	68,0	N/A	0,73	0,64	0,50	0,31	40	2,0	0,61	1,69	0,53	3,1	0,95
46	Dutchi Motors B.V.	DM1-	132 M6	4	960	400	/	690	Δ	Y	50	IP 55	71,3	F (temp. rise B (80 K))	82,3	81,6	78,6	67,5	N/A	0,79	0,71	0,58	0,38	40	1,8	0,55	1,52	0,47	3,6	1,14
92	Dutchi Motors B.V.	DM1-	132 M2	9	2870	400	/	690	Δ	Y	50	IP 55	75,0	F (temp. rise B (80 K))	86,3	87,0	86,1	80,1	N/A	0,89	0,86	0,78	0,61	30	2,3	0,72	1,70	0,53	3,3	1,05
94	Dutchi Motors B.V.	DM1-	132 MX4	9	1435	400	/	690	Δ	Y	50	IP 55	78,7	F (temp. rise B (80 K))	86,8	87,5	86,3	79,8	N/A	0,84	0,79	0,68	0,45	60	2,6	0,80	1,83	0,57	3,4	1,07
112	Dutchi Motors B.V.	DM1-	132 MX2	11	2895	400	/	690	Δ	Y	50	IP 55	78,5	F (temp. rise B (80 K))	88,5	88,8	87,3	79,9	N/A	0,90	0,85	0,72	0,44	36	2,6	0,80	1,90	0,59	3,7	1,15
114	Dutchi Motors B.V.	DM1-	132 MY4	11	1435	400	/	690	Δ	Y	50	IP 55	96,4	F (temp. rise F)	85,7	86,4	85,6	79,5	N/A	0,84	0,78	0,68	0,47	73,2	2,6	0,80	1,79	0,56	3,2	1,00

Extras / Options :

**voorbeelden - extra's**

- with AC-heater : 25Watt / 1~230V / 50Hz (JT/AC/1B)
- with PT100 element for the windings (3pcs)
- with PT100 element for the bearings (2pcs)
- with Forced Ventilator (see separate page)
- with Brake (see separate page)

TBV SCHEEPS CERTIFICAAT	
Your order no.:	hier invullen
Our order no.:	hier invullen
Our invoice no.:	hier invullen
soort	Ship execution below deck acc. Classification Bureau Veritas
IM	B3
remarks	3 x PTC 150°C
1	extra opties hier invullen
2	extra opties hier invullen









